



BLISTERPACK

AUTOMATIC BLISTER SEALER

Automatic blister sealing machine located over a belt conveyor. Manual placement of bubbles, product and cards. May be provided optionally with automatic bubble or card feeder. Manufactured in sizes varying from 7 7/8 " x 7 7/8 " to 11 7/8 " x 23 1/2 " .



Samples:



ELETRO-FORMING

Rua C. C. Oliveira, 280 Embú - SP - Brasil
Phone : 55 11 4704-3699 - Fax : 55 11 4704-3987
www.eleto-forming.com - E-mail : info@eleto-forming.com

PLC



CARDS FEEDER



GENERAL FEATURES

- Manual placement of the bubble, products and tablet.
- Automatic feed of bubbles and/or tablets optional.
- The Machine can be adapted to receive an automatic feeder of products.
- Machine of 16 continuous and automatic weld tools. Tools fixed in two chains and precisely indexed.
- Change of tools in 30 minutes.
- Pedal to stop operation.
- PLC of great capacity. Makes the control of weld temperature and time, has mould memory and parts counter.
- First class electric and pneumatic material.
- Eletro - Forming offers operation manual, electric and pneumatic plants and list of parts to become the maintenance easy.
- 1 year guarantee.

TECHNICAL FEATURES

Output.....700 cycles per hour.

Air compressed pressure.....8 bar.

Maximum sealing height.....70 mm.
(2 7/8 ").

Sealing force.....15,000 N.

Plastic grade.....PVC.

Maximum sealing area.....300 x 600 mm.
(11 7/8 " x 23 1/2 ").

Dimensions.....4.5 L x 1.2 W x 1.2 H m.
(177 " x 47 " x 47 ").

Installed power.....2500 W.

Maximum temperature.....250°C (480 F).

Electrical Consumption.....700W.

Weight.....700 Kg.

The above features may be changed in order to adjust the needs of each case.

ELETRO-FORMING

Rua C. C. Oliveira, 280 Embú - SP - Brasil
Phone : 55 11 4704-3699 - Fax : 55 11 4704-3987
www.eletro-forming.com - E-mail : info@eletro-forming.com